

ETERNABOND

EternaPrime

EternaBond EternaPrime is a specially formulated primer developed specifically for EternaBond tapes. EternaPrime is based on a VOC exempt solvent. EternaPrime meets all federal standards for health and environmental safety.

EternaPrime is designed to work with all EternaBond tapes and was specifically developed for preparation of surfaces when installing EternaBond tapes in low ambient temperatures from 40°F down to -20°F. It is also widely used as a coalescing agent on surfaces which have difficult to remove dirt or conditions which may encapsulate the EternaBond tape.

*Do not use on PVC.

Basic Use

EternaPrime is used to prepare surfaces for application of all EternaBond tapes. Recommended uses include, but are not limited to dirty surfaces which are difficult to clean completely (tar and gravel), potentially loose surfaces (mortar), porous surfaces (wood or concrete), and anytime the EternaBond tape is applied at temperatures below 40°F ambient.

Composition

EternaPrime is based on a VOC exempt solvent with a blend of our elastomers and resins infused into the solvent.

Technical Data

Application Temperature	-20°F – 205°F
Coverage	300+ Sq. Ft. per gallon
Drying Time at 60°F	15 Minutes
Film thickness	+/- 4 mils when wet
Flash Point	110°F
Standard can sizes	½ pint, 1 quart, 1 gallon
Standard case quantity	24 ½ pints per case, 12 quarts per case, 1 gal. per case.
Viscosity	135 – 152 cps
Weight	10 lbs. per gallon

Surface Preparation

Surface must be dry. Remove heavy accumulations of loose rust and scale, dust, talc, and dirt. Oil, grease, and other contaminants should be removed with EternaClean or a non-residue cleaner. Do not use EternaPrime on PVC roofs as reactivation of some plasticizers may occur.

Application

EternaPrime can be sprayed, rolled, or brushed onto surface (stir frequently).

ETERNABOND, Inc.

75 E. Division
Mundelein, IL, USA
Telephone: 888-336-2663
Fax: 847-837-9449
www.eterabond.com