

WindowSeal

Description

Use **WindowSeal** to seal all windows when installed regardless of surfaces being joined. **WindowSeal** creates a moisture tight, air and vapor barrier.

WindowSeal bonds to a wide range of surfaces including glass, wood, aluminum, vinyl, OSB, polyethylene, polypropylene, polystyrene, Tyvek™, fiberglass, brick, concrete, masonry, and virtually all construction materials.

Basic Use

WindowSeal tape is a self-sealing adhesive that creates a water tight seal between the window frame and virtually all structure surfaces. Irregular or curved surfaces are easy because **WindowSeal** is extremely conformable. **WindowSeal**, if kept warm (70° F ambient) prior to installation, can be installed at temperatures as low as 20° F ambient and as low as -20° F ambient with optimal **EternaPrime**. No staples or nails required.

Composition

WindowSeal utilizes **EternaBond's** advanced **MicroSealant Technology**, a 100% solids formulation of synthetic resins, thermoplastics and non-curing rubber with a built-in primer. It is bonded to a low density polyethylene (LDPE) backing. The adhesive coating is protected by a silicone release liner, to be removed prior to application.

Surface Preparation

Surface must be clean and dry. Moisture, dust, dirt or other foreign matter should be removed. Remove oil and grease, etc. with a suitable cleaner.

Technical Data	
Application temperature	150° F to -20° F ambient
Available widths	Up to 48"
Bacteria resistance	Excellent
Flexibility	1/2" radius at - 20° F
Fungal resistance	Excellent
Low temperature flexibility	Excellent
Peel adhesion	135 oz. /in width
Sag rating	>200° F
Shelf life	Up to 5 years
Standard case quantity	100 sq. ft. per case
Standard roll size	4", 6" x 50'
Temperature flexibility range	-70° F - >200° F
Total thickness	20 mils
Water absorption	Less than .05%
<small>Values are typical performance properties and characteristics based on laboratory testing. This is intended as a guide for comparison purposes and does not constitute a specification or specification range.</small>	

Application

Install **WindowSeal** over the repair area, removing the release liner gradually to prevent contamination of the adhesive prior to application. Rub or roll with pressure using your hand or steel roller to activate bonding process. This material may be applied to clean dry surfaces from 150° F to -20° F ambient. Treat surface with **EternaPrime** for installations from 40° F to -20° F ambient.

CAUTION: All statements and technical information in this document are based on tests or data that ADCO believes is reliable. However, ADCO does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of ADCO's products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of ADCO's product with the design, structure, and materials of the user's end product and the suitability of ADCO's product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.

EternaBond WindowSeal R1 02/15/12

ADCO Products, Inc
Michigan Center MI
800.248.4010 phone
517.764.0334 phone
517.764.6697 fax
www.adcocorp.com

EternaBond, Inc.
Mundelein IL, USA
888-336-2663 phone
847-837-9449 fax
www.eter nabond.com

WARRANTY: ADCO warrants its products to conform to ADCO's specifications at the time of sale when tested according to ADCO standards. If a product is proven to be defective when tested according to ADCO standards, ADCO will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYERS SOLE AND EXCLUSIVE REMEDY AGAINST ADCO AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall ADCO be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.

