

# ETERNABOND

## Pitch Pocket Sealant

EternaPocket Pitch Pocket Sealant is a one component, non-shrink sealant specifically designed for filling, sealing, and re-sealing all types of pitch pockets. EternaPocket Sealant is designed to be used in conjunction with EternaBond EternaPocket. One 28 oz. tube is specifically designed to fill one 4"X4" EternaBond EternaPocket.

Conventional quart tube packaging eliminates the requirement for custom application equipment, as well as waste associated with larger packaging. Performance range is -40° F to 200°F +.

EternaPocket Pitch Pocket Sealant bonds to a wide range of surfaces including difficult roof materials such as: EPDM, TPO, most PVC, CSPE/Hypalon, CPE, SBS, APP modifies, asphalt BURs, coal tar BURs, all metal roofs, tiles, shingle, aluminum, Galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.

### Basic Use

EternaPocket Sealant is designed to be used in conjunction with EternaBond EternaPocket. Because of EternaPocket Sealant's excellent ability to adhere to silicone, the Sealant is an ideal solution for sealing gutter seams, fasteners, or any areas where silicone has been applied in such a manner that makes it difficult to seal the area with EternaBond Tapes.

### Composition

EternaPocket Pitch Pocket Sealant is a 100% solids moisture-cure sealant. It is semi self-leveling, so that it can be used to fill pitch pockets, pans, and other applications with minimal tooling. The sealant is viscous enough to avoid drain out issues encountered with sealants having a more liquid consistency. EternaPocket Sealant's 100% solids formula results in zero shrinkage.

### Technical Data

Appearance	White liquid
Boiling Point	325° F
Color	White
Container Size	28 oz. Tube
Flash Point	315° F+
Odor	Lime
Shelf Life	1 Year
Stability	Stable

### Surface Preparation

Surface must be clean and dry. Moisture, dust, dirt, or other foreign matter should be removed. Remove oil and grease, etc. with EternaClean or a non residue cleaner such as acetone or lacquer thinner. Remove salt and other contaminants.

### Application

Cut the tip and puncture the seal of the caulk tube. Fill the EternaPocket pan with EternaPocket Pitch Pocket Sealant using a standard quart size caulk gun. One 28 oz. tube of Sealant will fill one 4"X4" pan. Slightly over fill the pan so that water does not sit in the pocket. Any unused Pitch Pocket Sealant can be saved by sealing the tip with tape or a plastic film.

### ETERNABOND, Inc.

75 E. Division  
Mundelein, IL, USA  
Telephone: 888-336-2663  
Fax: 847-837-9449  
[www.eterabond.com](http://www.eterabond.com)